



## Pallet Wrappers

Our range of pallet stretch-wrapping machines offers the ideal solution for wrapping medium to high-volume pallet quantities in a fully automatic format. The range caters for the full market spectrum of pallet loads, is designed and constructed for heavy duty operation, and fully conforms to European safety standards.

We guarantee the lowest costs in the UK and offer a free installation, delivery service and after-sales care service. Our pallet wrappers come supplied with a one-year parts and labour warranty and we offer a full spares and service back-up facility. Free trial periods are available upon request.

Ask our friendly team about our range of pallet wrap solutions, including our unique PolyLite and Polyair products.



### Power pre-stretch stretch wrap turntable

A fixed unit that automatically pre-stretches the film by up to 300% giving you impressive yield capacity.

#### Film carriage

- Easy load film system
- 0–300% pre-stretch function
- Photocell to detect top of pallet
- Safety switch on bottom of carriage to prevent crushing

#### Turntable

- 0–13 rpm adjustable for rotation speed
- Soft start and exact end positioning for easy loading
- Chain drive for durability and low maintenance

#### Column

- Foldable for transport/repositioning
- Chain drive to film carriage with 'parachute' safety brake
- Forklift access points for repositioning
- Mounting points for multi-position ramp
- Very strong box-section construction

#### Control

4 programmable menus adjustable for:

- Film tension, film overlap, turntable speed, number of top and bottom wraps, wrap height
- Top sheet mode
- Emergency stop safety switch and reset

#### Fully automatic

- Turntable diameter 1500mm
- Maximum wrapping height 2100mm
- Maximum load 2000kg

#### Options

- Loading ramp
- Metal frame to sink machine into floor

### Robo-wrapper

The robo-wrapper is self-propelled, powered by batteries, and only requires only 1 metre clear space around the pallet being wrapped. It wraps a standard pallet in as little as 45–60 seconds.

#### Benefits

- Fully automated, 0–300% pre-stretch function
- Elimination of load failures – consistently better wrapped loads
- Improved productivity

#### Performance

- Production speeds of 25 loads/hr
- User programmable wrap cycles
- Built-in film cutter which cuts film at completion of wrap cycle
- Adjustable carriage mast settings
- Wraps larger non-standard pallets

#### Film delivery

- Film tension adjusted electronically from the control panel
- Works with various types of film

#### Electrical data

- Driving voltage: 24V/DC
- Built-in battery charger: 110–120 VAC, single phase 60Hz
- Battery capacity – 200/300 pallets on a single charge

#### Operating controls

- Wrap up/down cycle
- Independent top and bottom wrap pattern selection
- Automatic and manual pallet height control

#### Safety

- Push/pull mushroom emergency stop button
- Contact safety edge which stops the wrapping arm if it inadvertently strikes an object
- Low voltage – 24V